PRODUCT DATA SHEET

CROWN GREASE MP

Grease MP is multi-purpose covering a wide variety of moderate service applications. It is formulated with a lithium soap base and solvent-refined high-viscosity index mineral base oils to act as the lubricant. It contains special chemical additives, which enhanced oxidation resistance and tower oil separation

BENEFITS

- · Long service life.
- Resistance to water washing in moderate conditions.
- · Good dispensing characteristics

APPLICATION

Grease MP is recommended for the lubrication of automotive chassis fittings and bearings and for general industrial lubrication where service conditions are moderate. It may be used in passenger cars, vans, trucks, farm tractors and general industrial equipment, machine tools and home appliances.

PROPERTIES	UNITS	VALUE		TEST METHOD
NLGI GRADE	-	2	3	-
Color	-	Light Brown	Light Brown	Visual
Texture	-	Smooth	Smooth	Visual
Thickener Type	-	Lithium	Lithium	-
Mineral Oil Viscosity @40°C	mm²/s	200.0	200.0	ASTM D-4052
Mineral Oil Viscosity @100°C	mm²/s	17.5	17.5	ASTM D-445
Dropping Point (min)	°C	190	195	ASTM D-2265
Worked Penetration @25°C	mm/10	265/295	220/250	ASTM D-217
Oil Separation % (max)	% mass	5.50	5	ASTM D-1742
Operating Temp	°C	-10 to 120		-
Product Code	-	001044	007044	-

PRODUCT CHARACTERISTIC



Version 2/2021