

## SPEEDX ULTRA SPX8

**Speedx Ultra SPX8** is the next generation ultimate performance fully synthetic multi-grade engine oil specially engineered to exceed the latest ILSAC GF-6A and API SP specifications. This is meant for current and future generation high performance engines specially those fitted with emission control devices. It is exclusively formulated with premium synthetic base fluids and unique environmental friendly additives system to provide exceptional thermal and oxidation stability that minimize oil thickening at very high operating temperature, with excellent deposits control and minimized engine wear and tear.

### BENEFITS

- Longer oil life & lower oil consumption with superior soot handling.
- Boost engine power and torque for better engine response and acceleration.
- Excellent fuel economy benefits.
- Ultimate engine wear protection at extreme driving conditions.
- Exceptional engine cleanliness - protects against engine sludge and varnish deposits.
- Resists viscosity and avoids thermal breakdown.
- Excellent cold engine starting - minimizes friction and wear at start-up.
- Superior protection of exhaust emission control system.

### PERFORMANCE LEVEL

#### APPROVED:

- API SP
- ILSAC GF-6A

### APPLICATIONS

Recommended for use in all types of modern passenger cars engine fitted with emission control devices which operates under extreme conditions.

### PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
<b>SAE GRADE</b>	-	<b>0W-20</b>	-
Specific Gravity @ 15 °C	-	0.8462	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	44.92	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	8.475	ASTM D-445
Viscosity Index	-	168	ASTM D-2270
Flash Point, COC	°C	222	ASTM D-92
CCS at -35 °C	cP	5850	ASTM D-5293
Base Number	mg KOH/g	8.5	ASTM D-2896
Color	-	2	ASTM D-1500
Pour Point	°C	-39	ASTM D-97
<b>Product Code</b>		<b>100042</b>	-

