

PRODUCT DATA SHEET

PREMIUM MOTOR OIL 40

PETROMIN PREMIUM MOTOR OIL Series is mono grade oils designed for gasoline engines. They provide excellent control over engine wear and deposit build-up and protection against rust and corrosion. Petromin Premium Motor Oils are blended from refined base oils, with detergent dispersant, anti-oxidant and anti-wear additives, which provide good protection against sludge and corrosion

BENEFITS

- Keep engines cleaner.
- Good protection against corrosion and wear.
- Good oxidation stability.

SPECIFICATIONS & APPROVALS

Petromin Premium Motor Oil 40 meets or exceeds the requirements of:

- API SJ

APPLICATIONS

PETROMIN PREMIUM MOTOR OIL Series is available in two viscosity grades for use in gasoline engines where oils conforming to API Service Category API SF/CC is required.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	40	-
Specific Gravity @ 15 °C	-	0.897	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	145.0	ASTM D-445
Viscosity @ 100 °C	mm ² /s	14.6	ASTM D-445
Viscosity Index	-	96	ASTM D-2270
Flash Point, COC	°C	252	ASTM D-92
Base Number	mg KOH/g	6.1	ASTM D-2896
Sulphate Ash	% wt	0.79	ASTM D-874
Color	-	3.0	ASTM D-1500
Pour Point	°C	-42	ASTM D-97
Product Code		1060	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

