

## PRODUCT DATA SHEET

### PETROBOARD TC WII

PETROMIN PETROBOARD 2-S Engine Oil is ash-less two-stroke engine oil formulated to meet the requirements of high-performance two stroke gasoline engines. It is pre-diluted to provide easier mixing with fuel and control spark plug fouling and combustion chamber deposit build-up.

#### BENEFITS

- Controls combustion chamber and spark plug deposits build-up.
- Excellent miscibility with gasoline.
- Keeps pistons, rings, plugs and exhaust ports clean.
- Resistance to low temperature gel formation.

#### SPECIFICATIONS & APPROVALS

Petromin Petroboard TC WII has the following Builder Approvals:

- NMMA (BIA) TC WII

#### APPLICATIONS

- It is recommended for high output two-stroke gasoline engines as well as for smaller engines fitted in scooters, motorcycles, lawn-movers, chainsaws, and other small equipment.
- It should be added with the gasoline in the ratio as recommended by the equipment manufacturer.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.880	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	35.62	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	6.19	ASTM D-445
Viscosity Index	-	138	ASTM D-2270
Flash Point, COC	°C	226	ASTM D-92
Base Number	mg KOH/g	8.65	ASTM D-2896
Color	-	Bluish Green	Visual
Pour Point	°C	-30	ASTM D-97
Sulphated Ash	% wt.	0.016	ASTM D-874
Product Code		<b>1160</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

