

SUPER BIKE 4T MBX5

Super Bike 4T MBX5 is a premium performance, shear-stable, multi-grade gasoline engine oil specifically designed for use in four-stroke motorcycles and portable power equipment requiring API SL JASO MA/MA2 Lubricants, including high output engines operating in severe service.

BENEFITS

- Prolongs engine life with anti-wear additive system.
- Saves on maintenance due to high oxidation stability.
- Resists oil breakdown under severe heat.
- Effective detergent/dispersant additive system ensures excellent control of piston ring deposits for very good power release and acceleration.
- Correct frictional characteristics enable smooth operation of wet clutches and back torque limiters.
- Shear stable VII additive minimizes thinning, and resists breakdown under high stresses for protection in both start-up and during high temperature operation.
- Superior anti-wear properties protecting the engine's most sensitive parts.

PERFORMANCE LEVEL MEETS:

- API SL
- JASO MA
- JASO MA2

APPLICATIONS

- Air and liquid-cooled four-stroke motorcycle engines.
- Motorcycles with and without oil immersed clutches, combined engine/transmission units or separate gear boxes, where a multi-grade engine oil is specified and motorcycles with back torque limiters.
- Suitable for Motorcycles with exhaust catalytic converters.
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE		TEST METHOD
SAE GRADE	-	20W-40	20W-50	-
Specific Gravity @ 15 °C	-	0.899	0.8728	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	134.1	170.87	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.45	19.7	ASTM D-445
Viscosity Index	-	119	133	ASTM D-2270
Flash Point, COC	°C	232	242	ASTM D-92
Base Number	mg KOH/g	6.14	6.14	ASTM D-2896
Pour Point	°C	-24	-27	ASTM D-97
Color	-	L 2.5	1.5	Visual
Product Code	-	123042	130042	-

