

## PRODUCT DATA SHEET

### EXTRA SUPER

PETROMIN EXTRA SUPER Motor oil is a high quality multi-grade lubricant for passenger cars and commercial vehicles. It is formulated from selected base oils and special chemical additives, which provide oxidation stability, and high degree of detergent and dispersant characteristics.

#### BENEFITS

- Can be used for all seasons.
- Excellent shear stability.
- Minimizes deposit formation at high temperatures.
- Protects against rust, wear and sludge formation.

#### SPECIFICATIONS & APPROVALS

Petromin Extra Super 20W-50 meets or exceeds the requirements of:

- API SJ

#### APPLICATIONS

PETROMIN EXTRA SUPER is recommended for supercharged or naturally aspirated gasoline engines, in passenger cars and commercial vehicles requiring the manufacturer's recommended API Service Category SJ. It can also be used where lower API level oils are recommended.

#### PRODUCT CHARACTERISTICS\*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	<b>20W-50</b>	-
Specific Gravity @ 15 °C	-	0.893	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	171.8	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	19.1	ASTM D-445
Viscosity Index	-	128	ASTM D-2270
Flash Point, COC	°C	240	ASTM D-92
Base Number	mg KOH/g	6.1	ASTM D-2896
Sulphated Ash	% wt.	2.5	ASTM D-874
Pour Point	°C	-18	ASTM D-97
Product Code		<b>1280</b>	

\*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

