PRODUCT

SPEEDX SPX4

Speedx SPX4 is a high quality multi-grade lubricant for passenger cars and commercial vehicles. It is formulated from selected base oils and special chemical additives which provide oxidation stability, and high degree of detergent and dispersant characteristics.

BENEFITS

- Can be used for all seasons.
- Excellent shear stability.
- Minimizes deposit formation at high temperatures.
- Protects against rust, wear and sludge formation

APPLICATIONS

Speedx SPX4 is recommended for supercharged or naturally aspirated gasoline engines, in passenger cars and commercial vehicles requiring the manufacturer's recommended API Service Category SJ. It can also be used where lower API level oils are recommended.

PRODUCT CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
SAE GRADE		-	20W-50	-
Specific Gravity @	2 15 ⁰C	-	0.8740	ASTM D-4052
Viscosity @	0 40 ℃	mm²/s	170.2	ASTM D-445
Viscosity @	0 100 ℃	mm²/s	19.53	ASTM D-445
Viscosity Index		-	134	ASTM D-2270
Flash Point, COC		°C	246	ASTM D-92
Pour Point		°C	-24	ASTM D-97
Base Number		mg KOH/g	6.10	ASTM D-2896
Color		-	2.0	-
Product Code		-	135042	-



Information and figures given here are typical of current production and conform to specification, minor variations may occur.

National Industries Park, PO Box-116636, Jebel Ali, Dubai, U.A.E. Tel: +971 6 597 9666 www.technolubeuae.com

PERFORMANCE LEVEL MEETS:

