SPEEDX PREMIUM SPX5

Speedx Premium SPX5 a new generation of automotive oils based on revolutionary concepts meeting the performance level required by today's gasoline engines. Speedx Premium SPX5 is blended with the most advanced additive package, which enables it to give exceptional performance under most severe operating conditions. It provides effective protection against oxidation, wear and corrosion under high temperature operations and remains a stable multigrade. Speedx Premium SPX5 provides good cold starting, low oil consumption and has high resistance to sludge formation.

BENEFITS

- Excellent engine protection
- · Eliminates seasonal oil changes.
- · Maintains a high order of engine cleanliness.
- · Better control of deposit formation
- · Better oxidation stability at high temperatures.
- · Excellent shear stability, maintain viscosity grade.
- · Protects against rust, wear and sludge formation
- · Suitable for mixed fleet operation

PERFORMANCE LEVEL

MEETS:

API SL

APPLICATIONS

Speedx Premium SPX5 is recommended for gasoline and diesel engine passenger and commercial vehicles of every make and type, turbocharged or naturally aspirated, which require API SL It exceeds the performance requirements of most European, Japanese and American car manufacturers

PRODUCT CHARACTERISTICS

| PROPERTIES | UNITS | VALUE | TEST METHOD |
|--------------------------|-----------|--------|-------------|
| SAE GRADE | - | 10W-40 | - |
| Specific Gravity @ 15 °C | - | 0.8603 | ASTM D-4052 |
| Viscosity @ 40 °C | mm²/s | 102.5 | ASTM D-445 |
| Viscosity @ 100 °C | mm²/s | 15.48 | ASTM D-445 |
| Viscosity Index | - | 160 | ASTM D-2270 |
| Flash Point, COC | °C | 228 | ASTM D-92 |
| Base Number | mg KOH/gm | 9.8 | ASTM D-2896 |
| Pour Point | °C | -33 | ASTM D-97 |
| Product Code | - | 149042 | - |

