

# PRODUCT DATA SHEET

## CROWN FORMULA FX-5

**Formula FX-5** is a new generation of automotive oils based on revolutionary concepts meeting the performance level required by today's gasoline engines, It is blended with the most advanced additive package, which enables it to give exceptional performance under most severe operating conditions.

### BENEFITS

- Excellent engine protection
- Eliminates seasonal oil changes.
- Maintains a high order of engine cleanliness.
- Better control of deposit formation
- Better oxidation stability at high temperatures.
- Excellent shear stability, maintain viscosity grade.
- Protects against rust, wear and sludge formation
- Suitable for mixed fleet operation.

### PERFORMANCE LEVEL

Meets and Exceeds:

- API SL

### APPLICATION

**Formula FX-5** is recommended for gasoline and diesel engine passenger and commercial vehicles of every make and type, turbocharged or naturally aspirated, which require API SL It exceeds the performance requirements of most European, Japanese and American car manufacturers.

### PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	<b>20W-50</b>	-
Specific Gravity @ 15 °C	-	0.894	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	165	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	19.0	ASTM D-445
Viscosity Index	-	130	ASTM D-2270
Flash Point, COC	°C	240	ASTM D-92
Pour Point	°C	-24	ASTM D-97
Base Number	mg KOH/gm	7.60	ASTM D-2895
Sulphated Ash	%wt.	0.99	ASTM D-874
Product Code	-	<b>156044</b>	-