

SPEEDX SPX3

Speedx SPX3 is a high quality multigrade lubricant for passenger cars and commercial vehicles. It is formulated from selected base oil and special chemical additive which provide oxidation stability, and high degree of detergent and dispersant characteristics.

BENEFITS

- Excellent oxidation stability.
- Improves anti-wear performance.
- Improved control of engine deposits.
- Better protection against rust and corrosion.

PERFORMANCE LEVEL

MEETS:

- API SG

APPLICATIONS

Speedx SPX3 Series is used in gasoline engines where oils conforming to API Service Category API SC is required.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	20W-50	-
Specific Gravity @ 15 °C	-	0.8926	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	178.0	ASTM D-445
Viscosity @ 100 °C	mm ² /s	19.70	ASTM D-445
Viscosity Index	-	127	ASTM D-2270
Flash Point, COC	°C	225	ASTM D-92
Sulphated Ash	m%	1.35	ASTM D-874
Base Number	mg KOH/g	10.71	ASTM D-2896
Pour Point	°C	-24	ASTM D-97
Product Code	-	161042	-

