

PRODUCT DATA SHEET

CROWN TURBOMAX TX-5

Turbomax TX-5 is a heavy-duty diesel engine oils and developed for moderate and high-output diesel engines, either naturally aspired or super-charged. They minimize deposits, reduce wear and impart dispersant and detergent properties. They are formulated from thermally stable mineral base oils and chemical additives to provide optimum control of deposits in severe service and control against wear, rust and corrosion.

BENEFITS

- Good control over deposits at high temperatures
- Improves fuel economy
- Good control over low temperature sludge
- Eliminates seasonal oil changes.
- Reduces oil consumption.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CF-4

APPLICATION

Turbomax TX-5 is recommended for use in moderate output diesel engines in commercial vehicles where manufacturer's specifications require API CF performance level oil.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	20W-50	-
Specific Gravity @ 15 °C	-	0.8937	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	184.9	ASTM D-445
Viscosity @ 100 °C	mm ² /s	20.53	ASTM D-445
Viscosity Index	-	130	ASTM D-2270
Flash Point, COC	°C	246	ASTM D-92
Pour Point	°C	-24	ASTM D-97
Sulphated Ash	%wt	1.32	ASTM D-874
Base Number	mg KOH/gm	10.20	ASTM D-2896
Color	-	L 3.0	ASTM D-1500
Product Code	-	164044	-