

PRODUCT DATA SHEET

CROWN FORMULA F-2

Formula F-2 is a monograde crank case gasoline lubricant for passenger car and light duty trucks under normal driving conditions. This oil is blended from a highly refined paraffinic base oils and incorporated with high quality additives.

BENEFITS

- Excellent Oxidation resistance.
- Improved anti-wear performance.
- Improved protection against engine deposits, rust & corrosion.
- Keep engine cleaner.

PERFORMANCE LEVEL

Meets and Exceeds:

- API SF/CD

APPLICATION

Formula F-2 Series is used in gasoline engines where oils conforming to API Service Category API SF is required.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	50	-
Specific Gravity @ 15 °C	-	0.9018	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	226.6	ASTM D-445
Viscosity @ 100 °C	mm ² /s	20.23	ASTM D-445
Viscosity Index	-	103	ASTM D-2270
Flash Point, COC	°C	256	ASTM D-92
Sulphated Ash	m%	0.94	ASTM D-874
Base Number	mg KOH/g	6.6	ASTM D-2896
Pour Point	°C	-9	ASTM D-97
Color	-	5.5	-
Product Code	-	178044	-