

PRODUCT DATA SHEET

DIESEL HD

PETROMIN DIESEL HD monograde diesel engine oil Series is designed for automotive and industrial use. Formulated from high quality base stocks and contain a balanced additive system which includes dispersants, detergents, rust inhibitors, anti-oxidant and anti-wear agents.

BENEFITS

- Cleaner engines.
- Protection against mechanical wear.
- Protection against low-temperature rusting and corrosive wear.

SPECIFICATIONS & APPROVALS

Petromin Diesel HD meets or exceeds the requirements of:

- API CF

APPLICATIONS

PETROMIN DIESEL HD oil Series is recommended for automotive diesel engines in light trucks, vans, pick-ups and buses as well as in lightly loaded stationary engines.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE			TEST METHOD
SAE GRADE	-	30	40	50	-
Specific Gravity @ 15 °C	-	0.893	0.897	0.900	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	90.22	146.20	210.80	ASTM D-445
Viscosity @ 100 °C	mm ² /s	10.73	14.78	18.35	ASTM D-445
Viscosity Index	-	103	100	96	ASTM D-2270
Flash Point, COC	°C	232	252	270	ASTM D-92
Base Number	-	-			-
Sulphated Ash	% wt.	0.71	0.71	0.71	ASTM D-874
Color	-	2.0	2.5	3.0	ASTM D-1500
Pour Point	°C	-18	-15	-15	ASTM D-97
Product Code	-	1930	1940	1950	-

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

