

PRODUCT DATA SHEET

PETROMOULD SR

PETROMIN PETROMOULD SR is blended from highly refined, solvent treated mineral base oils, advanced additives of polymerized esters to exhibit extreme pressure, and good lubricity properties.

PETROMOULD SR oil is free from chlorine, Sulphur and phosphorous hence becomes environment friendly.

PETROMOULD SR oil is ash less and burns off cleanly.

BENEFITS

- High thermal, oxidative and hydrolytic stability.
- Do not cause staining.
- Excellent bio stability properties.
- Optimum viscometric properties.

APPLICATIONS

Recommended for continues casting mould release applications.

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.888	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	316	ASTM D-445
@ 100 °C	mm ² /s	32.4	ASTM D-445
Viscosity Index	-	143	ASTM D-2270
Flash Point, COC	°C	226	ASTM D-92
Pour Point	°C	-9	ASTM D-97
Neutralization NO.	mg KOH/g	0.5	ASTM D-974
Product Code		1960	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

