

## 2T ENGINE OIL

**2T Engine Oil** is high quality two-stroke engine oil formulated from high quality, highly refined mineral oils and balanced additives to provide enhanced protection. These high performance oils are specially blended for all two-stroke gasoline engines requiring JASO FB level performance lubricants.

### BENEFITS

- Suitable for use in air-cooled and water-cooled two- stroke motorcycle engines.
- Good lubricity characteristics help in reduced wear
- Reduced spark plug fouling prolongs the spark plug life.
- Good exhaust port and piston cleanliness through controlled ash and carbon deposits thereby maintaining combustion efficiency and protection against power loss.

### PERFORMANCE LEVEL

#### MEETS:

- JASO FB

### APPLICATIONS

**2T Engine Oil** is air and liquid-cooled two-stroke motorcycle and tricycle engines without exhaust catalysts, where JASO FB performance oils are acceptable

### PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
<b>SAE GRADE (J1536)</b>	-	<b>F/M2</b>	-
Specific Gravity @ 15 °C	-	0.8844	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	72.18	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	9.730	ASTM D-445
Viscosity Index	-	115	ASTM D-2270
Flash Point, PMCC	°C	186	ASTM D-93
Sulphated Ash	m%	0.04	ASTM D-874
Pour Point	°C	-21	ASTM D-97
<b>Product Code</b>	-	<b>199042</b>	-

