

PERFOMAX HD4

Perfomax HD4 70 is high viscosity oil developed from the latest lubrication technology. It provides good control over high temperature deposits, sludge, rust, corrosion. It gives better performance in middle, old-age and refurbished engines, where heavier oils are preferred.

BENEFITS

- Excellent protection against the effects of high-sulfur diesel
- Improved resistance to ring sticking, ring and cylinder wear, valve and combustion deposits.
- Good control of high temperature deposits

PERFORMANCE LEVEL

MEETS:

- API CF

APPLICATIONS

Perfomax HD4 is recommended for use in diesel engines either naturally aspirated or supercharged. they provide good performance under conditions of high speed, high load, high-temperature operation which require API Service Category CF.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.89.75	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	345.7	ASTM D-445
Viscosity @ 100 °C	mm ² /s	31.27	ASTM D-445
Viscosity Index	-	127	ASTM D-2270
Flash Point, COC	°C	246	ASTM D-92
Pour Point	°C	-21	ASTM D-97
Sulphated Ash	%wt.	1.35	ASTM D-874
Base Number	mg KOH/g	10.0	ASTM D-2896
Product Code	-	209042	-

