

# PRODUCT DATA SHEET

## CROWN TURBOMAX T-4

**Turbomax T-4** is high viscosity oil developed from the latest lubrication technology. It provides good control over high temperature deposits, sludge, rust, corrosion. It gives better performance in middle, old-age and refurbished engines, where heavier oils are preferred.

### BENEFITS

- Excellent protection against the effects of high-sulfur diesel
- Improved resistance to ring sticking, ring and cylinder wear, valve and combustion deposits.
- Good control of high temperature deposits

### PERFORMANCE LEVEL

Meets and Exceeds:

- API CF

### APPLICATION

**Turbomax T-4** is recommended for use in diesel engines either naturally aspirated or supercharged. They provide good performance under conditions of high speed, high load, high-temperature operation which require API Service Category CF.

### PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
Specific Gravity @ 15 °C	-	0.89.75	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	345.7	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	31.27	ASTM D-445
Viscosity Index	-	127	ASTM D-2270
Flash Point, COC	°C	246	ASTM D-92
Pour Point	°C	-21	ASTM D-97
Sulphated Ash	%wt.	1.35	ASTM D-874
Base Number	mg KOH/g	10.0	ASTM D-2896
Product Code	-	209044	-