

PERFOMAX HD4

Perfomax HD4 Series heavy duty oil is developed primarily for high out, naturally aspirated or supercharged diesel engines, Operating under moderate conditions. Perfomax HD4 is formulated from High mineral base oils and chemical additives which provide dispersant, detergent, anti-oxidant, anti-wear, anti-rust properties.

BENEFITS

- Excellent protection against the effect of high-Sulphur fuels.
- Good control of high temperature deposits.
- Improved resistance to ring sticking, ring and cylinder wear, valve and combustion deposits
- Long engine life.

PERFORMANCE LEVEL

MEETS:

- API CF

APPLICATIONS

Perfomax HD4 is recommended for use in diesel engine fitted in automotive, agriculture and construction equipment's, operating in fleet and construction business where relatively moderate Sulphur fuel is used and other severe service factors are considered.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE		TEST METHOD
SAE GRADE	-	40	50	-
Specific Gravity @ 15 °C	-	0.8944	0.9031	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	141.5	240.8	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.60	20.4	ASTM D-445
Viscosity Index	-	114	98	ASTM D-2270
Flash Point, COC	°C	240	260	ASTM D-92
Pour Point	°C	-15	9	ASTM D-97
Sulphated Ash	%wt	1.49	1.49	ASTM D-874
Base Number	mg KOH/g	11.2	11.2	ASTM D-2896
Color	-	L 3.5	L 3.5	ASTM D-1500
Product Code	-	230042	240042	-

