

PERFOMAX HD2

Perfomax HD2 Series is high quality oil suitable for diesel engines, either naturally aspirated or supercharged. They provided good control over high temperature deposits, sludge, rust, corrosion and wear. Perfomax HD2 oils are formulated with chemically stable, high VI base stocks and chemical additives that impart dispersant and detergent properties and resistance to oxidation, corrosion, wear and rusting.

BENEFITS

- Improved control over high-temperature varnish deposits
- Minimize low temperature sludge build-up.
- Good protection against rust and corrosion.

PERFORMANCE LEVEL

MEETS:

- API CD

APPLICATIONS

Perfomax HD2 oil Series is recommended for use in diesel engines either naturally aspirated or supercharged. They provide good performance under conditions of high speed, high load, high-temperature operation which require API Service Category CD.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE		TEST METHOD
SAE GRADE	-	40	50	-
Specific Gravity @ 15 °C	-	0.9000	0.8989	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	158.0	201.0	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.74	19.62	ASTM D-445
Viscosity Index	-	102	111	ASTM D-2270
Flash Point, COC	°C	246	254	ASTM D-92
Pour Point	°C	-15	-12	ASTM D-97
Sulphated Ash	%wt	1.51	1.46	ASTM D-874
Base Number	mg KOH/g	11.2	11.1	ASTM D-2896
Color	-	3.5	3.5	ASTM D-1500
Product Code	-	257042	251042	-