

PRODUCT DATA SHEET

CROWN TURBOMAX TX-8

Turbomax TX-8 is premium top quality diesel engine oil meeting future, current and obsolete engine oil performance level, particularly European and American standards. It is an ideal mixed fleet engine oil meeting API C/-4/SL The additive chemistry used in manufacturing Turbomax TX-8 is performance proven in the field.

BENEFITS

- Mixed fleet engine oil for American, European and Japanese vehicles.
 - Universal engine oil for old and new diesel engine fuelled by both high and low sulphur diesel.
 - Proven field-tested engine oil meeting EGR criteria.
 - Excellent TBN retention.
- Effective control over high temperature piston deposits and soot accumulation due to lower ash content.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CI-4/CH-4/CF

APPLICATION

Turbomax TX-8 is mixed fleet engine oil for heavy-duty diesel vehicles and passenger cars. It is recommended engine oil for both on-highway and off-highway vehicles fitted with new engines for low emissions and old engines of conventional design fuelled by low and high sulfur diesel fuels.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	20W-50	-
Specific Gravity @ 15 °C	-	0.8797	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	181.2	ASTM D-445
Viscosity @ 100 °C	mm ² /s	20.35	ASTM D-445
Viscosity Index	-	131	ASTM D-2270
Flash Point, COC	°C	248	ASTM D-92
Pour Point	°C	-30	ASTM D-97
Base Number	mg KOH/gm	10.5	ASTM D-2896
Sulphated Ash(max)	% wt.	1.5	ASTM D-874
CCS Viscosity@ -15 °C	cP	8100	ASTM D-5293
Color	-	L 3.5	ASTM D-1500
Product Code	-	270043	-