

PRODUCT DATA SHEET

FLEET ENGINE OIL

Petromin Fleet Engine Oil is a high-quality engine oil. It is designed for use in passenger cars and light trucks and vans. It is recommended for engines where, OEM recommends heavier oil such as SAE 50, 20W-50 or 25W-50 grades. It gives better performance in middle, old-age, and refurbished engines, where heavier oils are preferred. The additive chemistry used in manufacturing the Petromin Fleet Engine Oil is performance proven in the field.

BENEFITS

- Excellent soot control for protection against abrasive wear and soot-induced oil thickening.
- Excellent dispersant capabilities, which will minimize sludge and varnish deposits.
- Reduce corrosion & wear in higher mileage vehicles.
- Better low temperature performance when compare, performance operating with mono-grade.
- Excellent resistance to viscosity & thermal breakdown at high temperatures, thus ensure lower oil top-up.
- Excellent wear protection.
- Excellent rust and bearing corrosion protection

SPECIFICATIONS & APPROVALS

Petromin Fleet Engine Oil meets or exceeds the requirements of:

- API SJ

APPLICATIONS

Petromin Fleet Engine Oil is recommended where API SJ oil and earlier service category are recommended. Before using, consult owner's manual of the vehicle for the OEM recommended viscosity grade and API Service Classification.



PRODUCT DATA SHEET

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	25W-50	-
Specific Gravity @ 15 °C	-	0.897	ASTM D-4052
Viscosity @ 100 °C	mm ² /s	19.51	ASTM D-445
Viscosity Index	-	108	ASTM D-2270
Flash Point, COC	°C	236	ASTM D-92
Pour Point	°C	-18	ASTM D-97
Color	-	L 3.0	ASTM D-1500
Product Code	-	2800	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

