

PRODUCT DATA SHEET

CROWN TURBOMAX TX-5

Turbomax TX-5 is high quality multi-grade heavy-duty diesel engine oil developed from the latest lubrication technology. They exceed and meet the performance requirements of naturally aspirated, supercharged, and turbo charged high output diesel engines.

BENEFITS

- Can be used for all seasons.
- Maintains high engine cleanliness.
- Greater control of deposit formations.
- Prolonged oil life due to high oxidation stability at high temperatures.
- Excellent shear stability, maintains its viscosity grade.
- Protects against rust, wear and sludge formation.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CF-4

APPLICATION

Turbomax TX-5 is recommended for use in moderate output diesel engines in commercial vehicles where manufacturer's specifications require API CF-4 performance level oil.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	15W-40	-
Specific Gravity @ 15 °C	-	0.8876	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	111.5	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.40	ASTM D-445
Viscosity Index	-	139	ASTM D-2270
Flash Point, COC	°C	238	ASTM D-92
Pour Point	°C	-27	ASTM D-97
Sulphated Ash	% wt.	1.323	ASTM D-874
Base Number	mg KOH/gm	10.0	ASTM D-2896
Color	-	2.5	ASTM D-1500
Product Code	-	286043	-