

## GEARBOX OIL MP

**Gearbox Oil MP** Series are high-quality gear lubricants blended from solvent-refined mineral base oils and selected chemical additives. Due to its high shear stability it provides excellent protection for gears and can be used over a wide range of temperatures. It also provides protection against foaming of oil, and wear and rusting of gears.

### BENEFITS

- Formulated for automotive high-speed gears
- Excellent lubrication without channeling at low temperatures.
- Suitable for heavy-duty service in truck and bus gears operating at high temperatures.
- Provides good protection against corrosion.

### PERFORMANCE LEVEL

Meets:

- API GL-4

### APPLICATIONS

Recommended for the type of service characteristics of gears, particularly hypoid, in passenger cars and other automotive equipment operated under high-speed/shock-load, high-speed/low torque, and low-speed/high-torque conditions.

### PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE		TEST METHOD
<b>SAE GRADE</b>	-	<b>90</b>	<b>140</b>	-
Specific Gravity @ 15 °C	-	0.8971	0.906	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	203.9	434.2	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	17.96	30.3	ASTM D-445
Viscosity Index	-	96	99	ASTM D-2270
Flash Point, COC	°C	246	236	ASTM D-92
Pour Point	°C	-12	-9	ASTM D-97
Color	-	L 2.5	L 3.0	ASTM D-1500
<b>Product Code</b>	-	<b>301042</b>	<b>302040</b>	-

