PRODUCT

GEARBOX OIL MP

Gearbox Oil MP Series are high-quality gear lubricants blended from solvent-refined mineral base oils and selected chemical additives. Due to its high shear stability it provides excellent protection for gears and can be used over a wide range of temperatures. It also provides protection against foaming of oil, and wear and rusting of gears.

BENEFITS

- Formulated for automotive high-speed gears
- Excellent lubrication without channeling at low temperatures.
- Suitable for heavy-duty service in truck and bus gears operating at high temperatures.
- Provides good protection against corrosion.

APPLICATIONS

Recommended for the type of service characteristics of gears, particularly hypoid, in passenger cars and other automotive equipment operated under high-speed/shock-load, high-speed/low torque, and low-speed/high-torque conditions.

PRODUCT CHARACTERISTICS

PROPERTIES		UNITS	VALUE	TEST METHOD
SAE GRADE		-	140	-
Specific Gravity @ 15 °C		-	0.9046	ASTM D-4052
Viscosity	@ 40 °C	mm²/s	412.3	ASTM D-445
Viscosity	@ 100 °C	mm²/s	28.63	ASTM D-445
Viscosity Index		-	97	ASTM D-2270
Flash Point, COC		°C	270	ASTM D-92
Pour Point		°C	-12	ASTM D-97
Color		-	3.0	ASTM D-1500
Product Code		-	309040	-

Information and figures given here are typical of current production and conform to specification, minor variations may occur.

יושנעפיוערפי NATIONALLUBE

National Industries Park, PO Box-116636, Jebel Ali, Dubai, U.A.E. Tel: +971 6 597 9666 www.technolubeuae.com

PERFORMANCE LEVEL Meets:

• API GL-1