PRODUCT

GEARBOX OIL MPX

Gearbox Oil MPX is high-quality gear lubricants blended from solvent-refined mineral base oils and selected chemical additives. Due to their high shear stability, they provide excellent protection for gears and can be used over a wide range of temperatures. They also provide protection against foaming of oil, wear and rusting of gears.

BENEFITS

- Formulated for automotive high-speed gears.
- Excellent lubrication without channeling at low temperatures.
- Suitable for heavy-duty service in truck and bus gears operating at high temperatures.
- Provide good protection against corrosion.

•

APPLICATIONS

Recommended for the type of service characteristics of gears, particularly hypoid, in passenger cars and other automotive equipment operated under high-speed/shock-load, high-speed/low torque, and low-speed/high-torque conditions.

PRODUCT CHARACTERISTICS

PROPERTIES VALUE UNITS **TEST METHOD** SAE GRADE 80W 85W-90 Specific Gravity @ 15 °C 0.888 0.897 ASTM D-4052 Viscosity @ 40 °C mm2/s 76.64 193.5 ASTM D-445 @ 100 °C mm²/s 9.61 17.65 ASTM D-445 Viscosity ASTM D-2270 Viscosity Index 103 98 Flash Point, COC °C 243 256 ASTM D-92 Pour Point °C -24 -18 ASTM D-97 L 2.0 3.0 **ASTM D-1500** Color **Product Code** 310042 320042

Information and figures given here are typical of current production and conform to specification, minor variations may occur.



National Industries Park, PO Box-116636, Jebel Ali, Dubai, U.A.E. Tel: +971 6 597 9666 www.technolubeuae.com

PERFORMANCE LEVEL Meets:

• API GL-4