

# PRODUCT DATA SHEET

## CROWN FORMULA F-2

**Formula F-2** is a monograde crank case gasoline lubricant for passenger car and light duty trucks under normal driving conditions. This oil is blended from a highly refined paraffinic base oils and incorporated with high quality additives.

### BENEFITS

- Excellent Oxidation resistance.
- Improved anti-wear performance.
- Improved protection against engine deposits, rust & corrosion.
- Keep engine cleaner

### PERFORMANCE LEVEL

Meets and Exceeds:

- API SF/CC

### APPLICATION

**Formula F-2** Series is used in gasoline engines where oils conforming to API Service Category API SF/CC are required.

### PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	40	-
Specific Gravity @ 15 °C	-	0.9004	ASTM D-4052
Viscosity @ 40 °C	mm <sup>2</sup> /s	161.3	ASTM D-445
Viscosity @ 100 °C	mm <sup>2</sup> /s	15.54	ASTM D-445
Viscosity Index	-	98	ASTM D-2270
Flash Point, COC	°C	245	ASTM D-92
Sulphated Ash	m%	0.94	ASTM D-874
Base Number	mg KOH/g	6.6	ASTM D-2896
Pour Point	°C	-18	ASTM D-97
Color	-	L 3.0	ASTM D-1500
Product Code	-	342044	-