# PRODUCT DATA SHEET

## **CROWN FORMULA F-2**

**Formula F-2** is a monograde engine oils developed for gasoline engine oil .They provide excellent control over engine wear and deposit build up and protection against rust and corrosion .

#### **BENEFITS**

- Excellent Oxidation resistance.
- Improved anti-wear performance.
- Improved protection against engine deposits, rust & corrosion.
- Keep engine cleaner

#### **PERFORMANCE LEVEL**

Meets and Exceeds:

API SF

#### **APPLICATION**

Formula F-2 series is used in gasoline engines where oils conforming to API Service Category API SF/CC are required.

### PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	50	-
Specific Gravity @ 15 °C	-	0.8981	ASTM D-4052
Viscosity @ 40 °C	$mm^2/s$	221.8	ASTM D-445
Viscosity @ 100 °C	mm²/s	20.51	ASTM D-445
Viscosity Index	-	108	ASTM D-2270
Flash Point, COC	ōC	254	ASTM D-92
Sulphated Ash	m%	1.12	ASTM D-874
Base Number	mg KOH/g	7.53	ASTM D-2896
Pour Point	ΘC	-9	ASTM D-97
Color	-	6.0	-
Product Code	-	365044	-

