PRODUCT

PERFORMANCE LEVEL

API SP

APPROVED:

SPEEDX ULTRA SPX7

Speedx Ultra SPX7 is a high-performance lubricant using fully synthetic technology, specially developed for Gasoline and Diesel car engines, meeting, and complying with the requirements of the latest direct injection engines and conventional engines as well.

BENEFITS

- Longer oil life & lower oil consumption with superior soot handling.
- Boost engine power and torque for better engine response and acceleration.
- · Excellent fuel economy benefits.
- Ultimate engine wear protection at extreme driving conditions.
- Exceptional engine cleanliness protects against engine sludge and varnish deposits.
- Resists viscosity and avoids thermal breakdown.
- Excellent cold engine starting minimizes friction and wear at start-up.
- · Superior protection of exhaust emission control system.

APPLICATIONS

- Recommended for all Hybrid Gasoline engines in cars and light vehicles.
- · All turbocharged and multi-valved engines.
- Suitable for most severe operating conditions, on highways, dense city traffic & in extreme weather conditions.
- Suitable & exceeds the performance requirements of most European, Japanese and American car manufacturers.

PRODUCT CHARACTERISTICS

PROPERTIES		UNITS	VALUE				TEST METHOD
SAE GRADE		-	5W-40	10W-30	10W-40	15W-40	-
Specific Gravity @ 15 °C		-	0.8495	0.8513	0.8538	0.8633	ASTM D-4052
Viscosity	@ 40 °C	mm²/s	90.69	73.72	103.9	108.9	ASTM D-445
Viscosity	@ 100 °C	mm²/s	14.74	11.87	15.58	14.64	ASTM D-445
Viscosity Index		-	170	157	159	139	ASTM D-2270
Flash Point, COC		°C	234	234	232	234	ASTM D-92
Base Number		mg KOH/g	-36	-36	-33	-30	ASTM D-2896
Pour Point		°C	7.3	7.3	7.3	7.3	ASTM D-97
Product Code			390042	294042	295042	297042	-

نانننيونالالوب I NATIONALLUBE

Information and figures given here are typical of current production and conform to specification, minor variations may occur.

National Industries Park, PO Box-116636, Jebel Ali, Dubai, U.A.E. Tel: +971 6 597 9666 www.technolubeuae.com