

PRODUCT DATA SHEET

A1 SUPER SYNTHETIC 0W-40

PETROMIN A-1 SUPER SYNTHETIC 0W-40 is a high performance lubricant using latest synthetic technology, incorporating a precisely balanced component system. Specially developed for all high performance engines used in various applications, complying with the stringent performance requirements. It provides exceptional cleaning power, wear protection and overall performance improvement in old and new engines.

BENEFITS

- Ensuring sustainable high performance, thus meeting the needs of the engines in term of extended and better oil drain intervals.
- Outstanding detergent properties to ensure greater cleanliness of the engine.
- High Viscosity Index resulting in stable viscosity during operation.
- Provides excellent overall performance.
- Provides exceptional cleaning power for dirty engines.
- Superior anti-wear properties protecting the engine's most sensitive parts.
- Superior cold start protection even at very low temperatures.

APPLICATIONS

- **PETROMIN A-1 SUPER SYNTHETIC 0W-40** recommended for all large and medium engines in passenger and commercial vehicles.
- Suitable for old and new vehicles operating in extreme operating conditions.
- Suitable & exceeds the performance requirements of most European, Japanese and American vehicle manufacturers.

SPECIFICATIONS & APPROVALS

PETROMIN A-1 SUPER SYNTHETIC 0W-40 meets or exceeds the requirements of:

- API SN



PRODUCT DATA SHEET

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	0W-40	-
Specific Gravity @ 15 °C	-	0.8462	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	88.18	ASTM D-445
Viscosity @ 100 °C	mm ² /s	15.07	ASTM D-445
Viscosity Index	-	185	ASTM D-2270
Flash Point, COC	°C	201	ASTM D-92
Base Number	mg KOH/g	8.2	ASTM D-2896
Product Code		3920	

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

