

SPEEDX SP4

Speedx SP4 is mono grade oil designed for gasoline cars & commercial vehicles .They provide excellent Control over engine wear and deposit build up and protection against rust and corrosion.

BENEFITS

- Keep engines cleaner
- Good protection against corrosion and wear
- Good Oxidation Stability
- Minimize Deposit formation at high temperature

PERFORMANCE LEVEL

MEETS:

- API SJ

APPLICATIONS

Speedx SP4 is recommended for super charges or naturally aspirated gasoline engines in passenger cars & commercial vehicle requiring API SJ categories.

PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	50	-
Specific Gravity @ 15 °C	-	0.9042	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	251.9	ASTM D-445
Viscosity @ 100 °C	mm ² /s	20.43	ASTM D-445
Viscosity Index	-	95	ASTM D-2270
Flash Point, COC	°C	256	ASTM D-92
Pour Point	°C	-12	ASTM D-97
Sulphated Ash	m%	0.95	ASTM D-874
Base Number	mg KOH/g	6.7	ASTM D-2896
Color	-	L6.0	ASTM D-1500
Product Code	-	395042	-

