

PRODUCT DATA SHEET

CROWN FORMULA FX-7

Formula FX7 is a high performance lubricant using fully synthetic technology, specially developed for Gasoline and Diesel car engines, meeting and complying with the requirements of the latest direct injection engines and conventional engines as well.

BENEFITS

- Reduced low temperature sludge build - up and high temperature deposits
- Maximizes short and long term engine performance.
- Outstanding thermal and oxidation stability.
- Improves engine efficiency, independently qualified.
- Reduced low temperature sludge build-up and high temperature deposits.
- Easier engine start up and reduced wear.
- High quality base oils help reduce the oil volatility and therefore the oil consumption.

PERFORMANCE LEVEL

Meets and Exceeds:

- API SP

APPLICATION

- Suitable for usage in all modern Gasoline Engine that uses direct fuel injections.
- All turbocharged and multi-valved engines.
- Suitable for most severe operating conditions, on highways, dense city traffic 5 in extreme weather conditions.
- Suitable & exceeds the performance requirements of most European, Japanese and American car manufacturers.

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	10W-30	-
Specific Gravity @ 15 °C	-	0.8682	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	78.2	ASTM D-445
Viscosity @ 100 °C	mm ² /s	11.7	ASTM D-445
Viscosity Index	-	143	ASTM D-2270
Flash Point, COC	°C	228	ASTM D-92
Base Number	mg KOH/gm	8.0	ASTM D-2896
Pour Point	°C	-33	ASTM D-97
Product Code	-	488044	-