

PRODUCT DATA SHEET

CROWN TURBOMAX ULTRA TX-4

Turbomax TX-4 is fully synthetic ultra-high performance diesel engine oil (UHPD) and formulated to conform to ACEA, API & original equipment manufacturers performance standards for modern heavy duty diesel engines. It is designed to offer fuel saving performance across a range of modern heavy duty diesel engines over extended drain intervals. for all commercial and industrial vehicles with diesel engines. This oil has been developed in order to meet the advanced technological standards and market requirements of extended drain intervals, advanced engine protection and exceptional savings on the fuel.

BENEFITS

- Absolute protection during oil change intervals that may exceed 150,000 Kms
- Advanced additive technology offers fuel saving performance over extended drain intervals, helping reduce operating costs, beside keep engine clean.
- Robust anti-wear additives offer increased engine protection and reduced maintenance downtime.
- High performance formulation promotes bore polishing protection and increased vehicle uptime.
- Protects against high temperature oil thickening under adverse and demanding driving conditions.
- Formulated to offer robust corrosion protection to bearings, helping increase engine service life.
- Good foam suppression performance aids reliable lubrication and component protection.
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures.

PERFORMANCE LEVEL

Meets and Exceeds:

- API CF
- ACEA E4/E7
- Daimler Chrysler MB228.5
- SCANIA LDF-3
- VOLVO VDS-3
- MTU TYPE-3
- MAN 3277
- MACK EO-N
- DAF Extended drain
- RVI RLD,RLD-2 RXD & RD-2
- DEUTZ DQC III-10

(Suitable for use)

- IVECO 18-1804 TFE

APPLICATION

- Recommended for use in all diesel engines vehicles including heavy duty truck and bus operations, especially where extended drains are required. The oil is backwards compatible for older engines.
- Diesel engines meeting Euro I, II, III, IV & V emission requirements and engines running under severe operating conditions. Suitable for use with NOx reduction systems.
- For the correct oil drain intervals, the relevant engine manual of the manufacturer must be consulted.

PRODUCT DATA SHEET

PRODUCT CHARACTERISTIC

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE	-	5W-30	-
Specific Gravity @ 15 °C	-	0.855	ASTM D-4052
Viscosity @ 40 °C	mm ² /s	71.8	ASTM D-445
Viscosity @ 100 °C	mm ² /s	12.12	ASTM D-445
Viscosity Index	-	167	ASTM D-2270
Flash Point, COC	°C	228	ASTM D-92
Pour Point	°C	-42	ASTM D-97
Base Number	mg KOH/gm	15	ASTM D-2896
Product Code	-	543044	-